



# STACK UNIT FOR SEMI-COMMERCIAL LAUNDRY APPLICATIONS

## CS10 - OPL

WASHER : 9,5KG / DRYER: 8,2 KG

### FEATURES

- Freestanding, can be installed on any floor and any level
- Double capacity in same floor space
- Top, front and side panels standard available in white
- Stainless steel outer and inner drum
- Door opens 180° for easy loading and unloading
- Redesigned soap box with 4 compartments
- 440 G-force extraction
  - removes more moisture
  - minimizes drying times and utility costs
- 6 wash programs including possibility of programming cycle modifier options
  - added prewash
  - extra wash time
  - extra rinse
- 5 drying programs

### OPTIONS

- Top, front and side panels in stainless steel
- Coin-operated version for vended laundry applications
- Liquid soap connection



OPTIONAL

## CS10 - PROGRAMMED FOR OPL

MODEL NUMBER	BT3JGASP403UW06 (white cabinet) BT3JGAJP403UW06 (white cabinet) BT3JGASP403UN06 (Stainless steel cabinet) BT3JGAJP403UN06 (Stainless steel cabinet)	BT3JGASG403UW06 (white cabinet) BT3JGAJG403UW06(white cabinet)
CONTROL	EVO7S	EVO7S
CONTROL LOCATION	10° front control	10° front control
DRUM		
CAPACITY (KG)	washer: 9,5 / dryer: 8,2	washer: 9,5 / dryer: 8,2
CYLINDER VOLUME (L)	washer: 96,8 / dryer: 198	washer: 96,8 / dryer: 198
MOTOR		
POWER (KW)	washer: 0,67 / dryer: 0,25	washer: 0,67 / dryer: 0,25
CABINET		
CYLINDER FINISH	galvanized / stainless steel	galvanized
COLOURS	white/ stainless steel	white
DOOR TYPE	window / solid	window
DRUM SPEED		
SPIN SPEED (RPM)	1200	1200
G-FORCE	440	440
HEATING		
ELECTRIC (KW)	washer: 4,5 / dryer: 4,8	washer: 4,5 / dryer: 4,8
CONNECTIONS		
ELECTRICAL REQUIREMENTS	400/50/3N (conversion to 230/50/3 possible)	400/50/3N (conversion to 230/50/3 possible)
EXHAUST OUTLET DIAMETER (MM)	102	102
EXHAUST AIRFLOW (L/SEC)	105	105
WATER INLET (IN)	0,75"	0,75"
WATER PRESSURE (BAR)	20-120	20/120
DRAIN	Pump	Gravity
OPERATION		
WATER CONSUMPTION PER CYCLE (L)	51,8*	51,8*
CYCLE INDICATOR LIGHTS	YES	YES
TRANSPORT DATA		
GROSS WEIGHT (KG)	189	189
NET WEIGHT (KG)	175	118
DIMENSIONS H X W X D (MM)	1986 x 683 x 704	1986 x 683 x 704
PACKING DIMENSIONS H X W X D (MM)	2032 x 762 x 864	2032 x 762 x 864
PACKED VOLUME (M³)	1,34	1,34
AGENCY APPROVALS	CE	CE

	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q
CS10	597	225	610	1690*	1460*	333*	38,1	704	52	1211*	1986*	203	391	683	813*	938*	368*

\* with leveling legs turned into base.

